

Material Safety Data Sheet (MSDS)

Series:
#0870, #0871
(All Labels)

MSDS # 0099
Revision 1

NFPA Rating: 1-2-0
HMIS Rating: 1-2-0-B

SECTION I

EMERGENCY TELEPHONE NO.

TRADE NAME (IF NONE, PUT CHEMICAL) CLEAR Caulk (High Performance Solvent Based)

(918) 825-5744 (24 Hrs.)

MANUFACTURER'S NAME AND TELEPHONE NO. Red Devil, Incorporated (918) 825-5744

ADDRESS (Number, Street, City, State, Zip Code) 4175 Webb Street, Pryor, Oklahoma 74361

SECTION II - HAZARDOUS INGREDIENTS

%	TLV	PEL	UNITS
---	-----	-----	-------

Toluene*** [108-88-3]	12.8	100	200	ppm
Lt. aliphatic solvent naphtha [64742-89-8]	26.2	400	500	ppm
Polyalicyclic resin	32.4	NE	NE	
Xylene (1330-20-7)	4.2	100	100	ppm
Non-hazardous ingredients*	<25	NA	NA	

*Unlisted ingredients are not considered hazardous under the OSHA Hazard Communication Standard (29 CFR 1910).

***See Sect. 313 statement in Sect. IX

VOC: 42%/wt. CARB Compliance: NO. Prop 65 Ingredients: YES
(Contains Toluene, known to the state of California to cause cancer or reproductive harm.)

SECTION III - PHYSICAL DATA

BOILING POINT (°F)	>193	SPECIFIC GRAVITY (H₂O=1)	0.9
VAPOR PRESSURE (MM Hg.)	<120	PERCENT VOLATILES BY VOLUME (%)	<50
VAPOR DENSITY (AIR=1)	>1	pH	NA
SOLUBILITY IN WATER	Insoluble	EVAPORATION RATE	<1 (Ether = 1)

APPEARANCE AND ODOR Clear thick liquid/sealant consistency; solvent odor

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	<100°F (CC)	FLAMMABLE LIMITS	LEL	1%	UEL	8%
EXTINGUISHING MEDIA	Dry chemical, foam, or carbon dioxide					
SPECIAL FIRE FIGHTING PROCEDURES	Wear self-contained breathing apparatus (SCBA)					
UNUSUAL FIRE AND EXPLOSION HAZARDS	Vapors can flow to ignition sources and flashback.					

NA - Not Applicable

NE - Not Established

UN - Unavailable

