

CASTROL INDUSTRIAL WEST INC -- MOLY DEE TAPPING FLUID CUTTING OIL -- 9150-00N072614

=====
MSDS Safety Information
=====

FSC: 9150
MSDS Date: 08/28/1990
MSDS Num: CBYPX
LIIN: 00N072614
Tech Review: 09/03/1996
Product ID: MOLY DEE TAPPING FLUID CUTTING OIL
Responsible Party
Cage: CASTI
Name: CASTROL INDUSTRIAL WEST INC
Address: 5511 DISTRICT BLVD
City: LOS ANGELES CA 90040 US
Info Phone Number: 213-771-2257
Emergency Phone Number: 213-771-7000
Preparer's Name: A. LUM
Review Ind: N

=====
Contractor Summary
=====

Cage: CASTI
Name: CASTROL INDUSTRIAL INC
Address: 1001 W 31ST
City: DOWNERS GROVE IL 60515-1280 US
Phone: 708-241-4000
Cage: 98308
Name: CASTROL INDUSTRIAL NORTH AMERICA INC.
Address: 5511 DISTRICT BLVD
City: LOS ANGELES CA 90040 US
Phone: 213-890-4420

=====
Ingredients
=====

Cas: 64741-96-4
RTECS #: PY8040001
Name: MINERAL OIL, PETROLEUM DISTILLATES, SOLVENT REFINED (SEVERE), HEAVY
NAPHTHENIC, (ING 2)
% by Wt: 10-30
OSHA PEL: 5 MG/M3 (MFR)
ACGIH TLV: 5 MG/M3 (MFR)
Ozone Depleting Chemical: N

Name: ING 1:(SEVERELY SOLVENT REFINED PETROLEUM OIL)

Cas: 63449-39-8
RTECS #: RV0450000
Name: PARAFFIN WAXES AND HYDROCARBON WAXES, CHLORINATED; (CHLORINATED
PARAFFIN)
% by Wt: 30-50
OSHA PEL: N/K (FP N)
ACGIH TLV: N/K (FP N)
Ozone Depleting Chemical: N

=====
Health Hazards Data
=====

LD50 LC50 Mixture: LD50 (ORAL, RAT):> 5 G/KG
Route Of Entry Inds - Inhalation: NO
Skin: NO

Ingestion: NO
 Carcinogenicity Inds - NTP: NO
 IARC: NO
 OSHA: NO

Effects of Exposure: INHAL:TLV FOR PRODUCT NOT ESTABLISHED. REFER TO HAZARDOUS MATERIALS LIST FOR INGREDIENT TLV'S. SKIN:CONCENTRATE IS NOT EXPECTED TO CAUSE SKIN IRRITATION. SKIN ABSORPTION:CONCENTRATE IS NOT EXPECTED TO BE TOXIC. LD 50 (RABBIT) IS GREATER THAN 2 G/KG. EYE:CONCENTRATE IS NOT EXPECTED TO CAUSE EYE (EFTS OF OVEREXP)

Explanation Of Carcinogenicity: NOT RELEVANT.

Signs And Symptoms Of Overexposure: HLTH HAZ: IRRITATION. INGESTION: CONCENTRATE IS NOT EXPECTED TO BE TOXIC.

Medical Cond Aggravated By Exposure: NONE KNOWN.

First Aid: EYES: IN CASE OF CONTACT, FLUSH WITH PLENTY OF WATER. GET MEDICAL ATTENTION IF IRRITATION OCCURS. SKIN: WASH EXPOSED AREAS WITH SOAP AND WATER, IF IRRITATION OCCURS, GET MEDICAL ATTENTION. WASH CLOTHING BEFORE REUSE. INHALATION: IF IRRITATION OCCURS, REMOVE TO FRESH AIR AREA AND AVOID FURTHER INHALATION. INGESTION: GET MEDICAL ATTENTION IMMEDIATELY.

=====
 Handling and Disposal
 =====

Spill Release Procedures: RECOVER FREE LIQUID. KEEP PETROLEUM PRODUCTS OUT OF STREAMS AND WATERWAYS BY DIKING OR IMPOUNDING. ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER SEWERS, WATERCOURSES OR EXTENSIVE LAND AREAS.

Neutralizing Agent: NONE SPECIFIED BY MANUFACTURER.

Waste Disposal Methods: DISPOSAL MUST BE IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL REGULATIONS (FP N).

Handling And Storage Precautions: AVOID CONTACT W/EYES & BRTHG MISTS. WASH SKIN W/SOAP & H*2O AFTER CONTACT, BEFORE BREAKS & MEALS, & AT END OF WORK. WASH CONTAMD CLTHING BEFORE REUSE.

Other Precautions: DO NOT TAKE INTERNALLY. BRING PROD TO ROOM TEMP BEFORE USE. KEEP DRUMS CLSD WHEN NOT IN USE. PROT MEASURES FOR REPAIR & MAINTAINANCE OF CONTAMD EQUIP: WEAR GLOVES & PROT EYEWEAR AT ALL TIMES DURING EQU IPMENT DECONTAMINATION OR REPAIR.

=====
 Fire and Explosion Hazard Information
 =====

Flash Point Method: COC

Flash Point Text: 325F,163C

Extinguishing Media: CO*2, FOAM, DRY CHEMICAL.

Fire Fighting Procedures: USE NIOSH APPROVED SCBA & FULL PROTECTIVE EQUIPMENT (FP N).

Unusual Fire/Explosion Hazard: NONE KNOWN.

=====
 Control Measures
 =====

Respiratory Protection: IF EXCESSIVE MISTING OCCURS, OR IF ASSOCIATED TLV IS EXCEEDED, PROVIDE NIOSH APPROVED RESPIRATORY EQUIPMENT WITH TC-21C-XXX CARTRIDGE COMBINATION.

Ventilation: NORMALLY NOT NEEDED. USE LOC EXHST TO CAPTURE VAP, MIST & FUMES. PROVIDE > 60 FPM FACE VELOCITY FOR CONFINED SPACES.

Protective Gloves: CHEMICAL RESISTANT.

Eye Protection: ANSI APPROVED CHEM WORKERS GOGGS (FP N).

Other Protective Equipment: ANSI APPRVD EMER EYE WASH & DELUGE SHOWER (FP N). WEAR GLOVES & PROT EYEWARE AT ALL TIMES DURING EQUIPMENT (SUPDAT)

Work Hygienic Practices: WASH SKIN WITH SOAP & WATER AFTER CONTACT, BEFORE BREAKS & MEALS, & AT END OF WORK. WASH CONTAMD CLOTHING BEFORE REUSE.

Supplemental Safety and Health: VP: NEGLIGIBLE AT ROOM TEMPERATURE. EVAP

RATE: NEGLIGIBLE AT ROOM TEMPERATURE (BUTYL ACETATE =1). OTHER PROT
EQUIP: DECONTAMINATION OR REPAIR. APRON.

=====
Physical/Chemical Properties
=====

B.P. Text: >500F,>260C
Vapor Pres: SUPDAT
Spec Gravity: 1.06 (H*20=1)
Evaporation Rate & Reference: SUPDAT
Solubility in Water: % BY WT INSOLUBLE
Appearance and Odor: DARK GRAY OIL, SLIGHT OIL ODOR.
Percent Volatiles by Volume: 70.90
=====

Reactivity Data
=====

Stability Indicator: YES
Stability Condition To Avoid: NONE SPECIFIED BY MANUFACTURER.
Materials To Avoid: STRONG OXIDIZING AGENTS.
Hazardous Decomposition Products: OXIDES OF CARBON, SULFUR, MOLYBDENUM AND
HCL ARE POTENTIAL COMBUSTION PRODUCTS.
Hazardous Polymerization Indicator: NO
Conditions To Avoid Polymerization: NOT RELEVANT.
=====

Toxicological Information
=====

Ecological Information
=====

MSDS Transport Information
=====

Regulatory Information
=====

Other Information
=====

HAZCOM Label
=====

Product ID: MOLY DEE TAPPING FLUID CUTTING OIL
Cage: CASTI
Company Name: CASTROL INDUSTRIAL INC
Street: 1001 W 31ST
City: DOWNERS GROVE IL
Zipcode: 60515-1280 US
Health Emergency Phone: 213-771-7000
Date Of Label Review: 09/03/1996
Label Date: 09/03/1996
Chronic Hazard IND: N
Eye Protection IND: YES
Skin Protection IND: YES
Signal Word: CAUTION
Respiratory Protection IND: YES
Health Hazard: None
Contact Hazard: None
Fire Hazard: Slight
Reactivity Hazard: None
Hazard And Precautions: ACUTE: INHALATION: TLV FOR PRODUCT NOT
ESTABLISHED. REFER TO HAZARDOUS MATERIALS LIST FOR INGREDIENT TLV'S.

SKIN: CONCENTRATE IS NOT EXPECTED TO CAUSE SKIN IRRITATION. SKIN
ABSORPTION: CONCENTRATE IS NOT EXPTCEED TO BE TOXIC. LD 50 (RABBIT) IS
GREATHER THAN 2 G/KG. EYE: CONCENTRATE IS NOT EXPECTED TO CAUSE EYE
IRRITATION. INGESTION: CONCENTRATE IS NOT EXPECTED TO BE TOXIC. CHRONIC:
NONE SPECIFIED BY MANUFACTURER.

=====
Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of
Defense. The United States of America in no manner whatsoever expressly
or implied warrants, states, or intends said information to have any
application, use or viability by or to any person or persons outside the
Department of Defense nor any person or persons contracting with any
instrumentality of the United States of America and disclaims all
liability for such use. Any person utilizing this instruction who is not
a military or civilian employee of the United States of America should
seek competent professional advice to verify and assume responsibility
for the suitability of this information to their particular situation
regardless of similarity to a corresponding Department of Defense or
other government situation.